



INSTRUCTIONS FOR USING FOLGOS **ecoAGRO** FILM



Transport the film in an upright position. Special care must be taken to ensure that the film does not become crushed, dented or cut during handling and transportation of the reels.



Keep the film upright in the original carton.




The storage place should be roofed, dry, protected from sunlight (UV rays) and other atmospheric factors such as rain, snow, hail. The optimum storage temperature is 20°C, the minimum acceptable is 5°C.




Immediately before wrapping the bale the film should be at an optimum temperature of around 20°C for at least 24 hours.

Handle the packaging gently. To prevent damage, remove the reel carefully, immediately before use.




The recommended stretch of the film is 50% - 70%. To check the correct stretch, mark 2 points on the reel of film at a distance of 10 cm, after passing through the stretching rollers on the wrapping machine, the points should be 15 to 17 cm apart. To ensure optimum stretch, the machine rollers should be inspected and cleaned regularly.

INSTRUCTIONS FOR USING FOLGOS **ecoAGRO** FILM



Recommended overlapping of min. 50%, 4 to 6 layers at high moist matter. Drier bales require more layers min. 6. It is not recommended to bale in very dusty surroundings, which negatively affects the stickiness of the film, as well as the hermeticity of the bale and as a result the quality of the silage itself. Bales should be wrapped up to 2 hours after being formed.



Special attention must be paid to the sharpness and condition of the cutting knives to ensure good adhesion of the film and to eliminate long film tails.



The maximum number of bale layers is 3. For bales containing moist matter, 1 layer is recommended. Bales should be inspected regularly and any damage should be secured immediately. Store bales on dry ground, away from trees and watercourses. UV protection period is 12 months after wrapping.



Bales should be protected against corrosive substances and animals (e.g. rodents, birds). It is recommended to use a protective net.

To keep the warranty please follow the instruction.